

Bar Refrigeration

TBR60-RISZ1-L-B-11-2

Bar Refrigerator, Black Ext, 2 Glass Slide Doors



Dimensions	
External Width (mm)	1524
External Depth (mm)	631
External Height (mm)	881
Exclusions	Depth does not include 16 mm for door handle. Height does not include 7 mm for leg levelers.
Gross Volume (Litres)	550
Supplied Shelves	6
Shelf Size (L x D mm)	540 x 458
Internal Net Height (mm)	730
Unpackaged Weight (kg)	164
Packaged Weight (kg)	175
Packaged Dimensions (W x D x H mm)	1690 x 724 x 1067
Supplied with	Levelling Screws. Optional castors sold seperately.

Build	
Door Description	2 Full Glass Slide Doors
Exterior Construction	Black powder coated steel front. Matching black coated Aluminium sides & rear. Stainless steel countertop.
Interior Construction	Stainless Steel
Air Intake Position	Front
Ventilation Position	Front
Clearance Required	Zero back and sides
Cord Length (Meters)	3.04
Internal Lighting	TruLumina®
Standard w/ Locks	Not Standard. Options available.

Technical	
Temperature Range	0.5 : 3.3°C
Refrigerant	R290
Voltage/Frequency/Phase	220-240V/50-60Hz/1
Amps	1.3
Watts	299
Defrost Type	Auto



Specifications subject to change without notice.
Chart dimensions rounded up to the next whole millimeter (inches rounded up to the 1/8")

UK & Ireland
EMEA
Australia

0800 783 2049
[+41 61 563 07 05](tel:+41615630705)
[+61 2 9619 9999](tel:+61296199999)

TFIUK@truemfg.com
TrueCHCustomerService@truemfg.com
TrueRefAus@truemfg.com



TBR60-RISZ1-L-B-11-2

Technical drawings of the 1000 Series Walk-In Cooler, showing front, side, and detail views with dimensions in inches and millimeters.

Front View:

- Overall Width: 60" [1524]
- Overall Height: 34 11/16" [881]
- Top Panel Height: 1 3/4" [44]
- Right Panel Height: 25 17/32" [648]
- Bottom Panel Height: 25/32" [20]
- Left Panel Width: 11 19/32" [294]
- Right Panel Width: 2 3/16" [56]
- Interior Width: 42 9/16" [1081]
- Glass Door Viewing Area: 19 9/32" [490] X 22 31/32" [584]

Side View:

- Overall Depth: 10 31/32" [278]
- Top Panel Depth: 18 1/2" [470]
- Right Panel Depth: 19 7/16" [494]
- Bottom Panel Depth: 6" [152]
- Power Cord Exit Location: Indicated on the right panel.

Detail View (Access Opposite Condensing Unit):

- Overall Width: 25 1/2" [648]
- Overall Height: 24 27/32" [631]
- Top Panel Height: 20 3/4" [527]
- Right Panel Height: 30 27/32" [783]
- Bottom Panel Height: 22 3/4" [578]
- Left Panel Width: 24 21/32" [626]
- Right Panel Width: 3 15/16" [100]
- Access Opposite Condensing Unit: Indicated by a circle and arrow.
- Access Opposite Condensing Unit: 4 5/16" [110]
- Access Opposite Condensing Unit: 3 15/16" [100]
- Access Opposite Condensing Unit: 22 3/4" [578]
- Access Opposite Condensing Unit: 24 21/32" [626]
- Access Opposite Condensing Unit: 20 3/4" [527]
- Access Opposite Condensing Unit: 30 27/32" [783]
- Access Opposite Condensing Unit: 24 27/32" [631]
- Access Opposite Condensing Unit: 25 1/2" [648]

Detail View (Floor Access):

- Overall Width: 44 13/32" [1128]
- Overall Height: 18 3/4" [476]
- Top Panel Height: 7 3/4" [197]
- Right Panel Height: 4 11/32" [111]
- Bottom Panel Height: 16 3/4" [426]
- Left Panel Width: 1 3/8" [35]
- Right Panel Width: 4 31/32" [126]
- Access Opposite Condensing Unit: 3 15/16" [100]
- Access Opposite Condensing Unit: 4 5/16" [110]
- Access Opposite Condensing Unit: 22 3/4" [578]
- Access Opposite Condensing Unit: 24 21/32" [626]
- Access Opposite Condensing Unit: 20 3/4" [527]
- Access Opposite Condensing Unit: 30 27/32" [783]
- Access Opposite Condensing Unit: 24 27/32" [631]
- Access Opposite Condensing Unit: 25 1/2" [648]



Chart dimensions rounded up to the next whole millimeter (inches rounded up to the 1/8")

TFIUK@truemfg.com
TrueCHCustomerService@truemfg.com
TrueRefAus@truemfg.com

