

# TUC-27G-HC~FGD01

 Undercounter Foodservice Refrigerator, 1 Glass Swing Door



| Dimensions                         |                                                                                                          |
|------------------------------------|----------------------------------------------------------------------------------------------------------|
| External Width (mm)                | 702                                                                                                      |
| External Depth (mm)                | 766                                                                                                      |
| External Height (mm)               | 839                                                                                                      |
| Exclusions                         | Depth does not include 26mm for rear bumpers and 42mm for door handle.                                   |
| Net Volume (Litres)                | 143                                                                                                      |
| Gross Volume (Litres)              | 184                                                                                                      |
| Display Area (m <sup>2</sup> )     | 0.32                                                                                                     |
| Supplied Shelves                   | 2                                                                                                        |
| Shelf Size (L x D mm)              | One 590 x 488 + One 590 x 349                                                                            |
| Internal Net Height (mm)           | 630                                                                                                      |
| Unpackaged Weight (kg)             | 82                                                                                                       |
| Packaged Weight (kg)               | 93                                                                                                       |
| Packaged Dimensions (W x D x H mm) | 769 x 839 x 1207                                                                                         |
| Supplied with                      | Heavy duty lock-in-place ø 64 mm castors (83 mm height) (reduced height option available, totals 810 mm) |

| Build                 |                                                            |
|-----------------------|------------------------------------------------------------|
| Door Description      | 1 Full Glass Swing Door                                    |
| Door Opening          | Right (standard) or Left                                   |
| Exterior Construction | Stainless steel front & countertop, aluminium sides & rear |
| Interior Construction | Clear coated aluminium, stainless steel base               |
| Air Intake Position   | Front                                                      |
| Ventilation Position  | Front                                                      |
| Clearance Required    | Zero back and sides                                        |
| Cord Length (Meters)  | 2.13                                                       |
| Internal Lighting     | LED                                                        |
| Standard w/ Locks     | Standard                                                   |

| Technical                      |                                                                                    |
|--------------------------------|------------------------------------------------------------------------------------|
| Temperature Range              | 0.5 : 3.3°C                                                                        |
| Refrigerant                    | R290                                                                               |
| Voltage/Frequency/Phase        | 220-240V/50-60Hz/1                                                                 |
| Amps                           | 0.8                                                                                |
| Watts                          | 184                                                                                |
| Temperature Class              | M1                                                                                 |
| Operating Statement            | Heavy Duty: This appliance is intended for use in ambient temperatures up to 40°C. |
| Test Standard                  | EN 23953                                                                           |
| EEC                            | A                                                                                  |
| Energy Efficiency Index        | 8.3                                                                                |
| Defrost Type                   | Auto                                                                               |
| Energy Consumption (kWh/24h)   | 1.25                                                                               |
| Energy Consumption (kWh/Annum) | 458                                                                                |



Specifications subject to change without notice.

Chart dimensions rounded up to the next whole millimeter (inches rounded up to the 1/8")

UK & Ireland  
EMEA  
Australia


0800 783 2049  
+41 61 563 07 05  
+61 2 9619 9999

TFIUK@truemfg.com  
TrueCHCustomerService@truemfg.com  
TrueRefAus@truemfg.com



## TUC-27G-HC~FGD01

 Undercounter Foodservice Refrigerator, 1 Glass Swing Door



Specifications subject to change without notice.

Chart dimensions rounded up to the next whole millimeter (inches rounded up to the 1/8")

UK & Ireland  
EMEA  
Australia

0800 783 2049  
+41 61 563 07 05  
+61 2 9619 9999

[TFIUK@truemfg.com](mailto:TFIUK@truemfg.com)  
[TrueCHCustomerService@truemfg.com](mailto:TrueCHCustomerService@truemfg.com)  
[TrueRefAus@truemfg.com](mailto:TrueRefAus@truemfg.com)

