

**KBEST.11.1006**

**Premium Combi Oven - Stacked Electric, 10 x 1/1 GN + 6 x 1/1 GN**

**Product Information**

- Compact unit at only 519mm wide (30% less space required than traditional ovens)
  - Symbiotic Steam (patented) innovative, heavy duty, highly efficient, dual boiler generation and steam injection oven
  - Steam Tuner (patented) exclusive feature allows actual tuning of saturated steam
  - Meteo System (patented) for precise control and saturation levels
  - Automatic descaling system for oven and boiler
  - Integrated recirculating cleaning via tablet, with liquid detergent dispenser installed if preferred
  - Large 7" innovative touch screen interface
  - Over 120 pre-set cooking programs, 1,000+ additional programs - 9 phase memory available
  - Automatic, adaptive cooking. Featuring rack control, regeneration, sous vide and smoking programs
  - Easy Service function, Recipe tuner, and Chef's note software all as standard
  - 6-speed inverter controlled fan for increased precision, control and reliability
  - LED lighting for superior cavity illumination
  - USB connection, HACCP
  - Supplied with multi-point core temperature probe, drain kit and advanced scale reduction filter
  - Left hand hinge door option available
  - All combi ovens are supplied with either Standard or Reverse Osmosis Filtration system
- **24-month warranty (Terms and conditions apply)**



**Specification Stacked**

<b>Standard Filter</b>	KBEST.11.1006.SF
<b>Reverse Osmosis</b>	KBEST.11.1006.RO
<b>W x D x H (mm)</b>	531 x 917 x 1978*
* Dimensions do not include water filtration system	
<b>Weight</b>	229kg
<b>Total Connected Load</b>	22.7kW
<b>Cold Water Connection</b>	3/4 BSP 150-350 kpa Min 10°C - Max 30°C
<b>Water Quality Requirements</b>	<b>Hardness:</b> 60-100ppm <b>TDS:</b> <100mg/L <b>Cl Chloride:</b> <32mg/L

**Specification Ovens**

<b>Model</b>	KB101WT (Top Oven)	KB061WT (Bottom Oven)
<b>Capacity</b>	10 x 1/1 GN Pans	6 x 1/1 GN Pans
<b>Total Connected Load</b>	14.8kW (25A circuit)	7.9kW (20A circuit)
<b>Electrical Connection</b>	3Ø + N + E 415VAC / 50Hz L1 = 20.7A / L 2 = 22.8A / L3 = 18.3A	3Ø + N + E 415VAC / 50Hz L1 = 10.4A / L 2 = 13.7A / L3 = 9.2A

**Legend:**

- A Electrical Connection
- B Steam Generation Water Inlet 3/4" BSP
- C Wash System Water Inlet 3/4" BSP
- D Drain Connection 32mm
- E Humidity Vent
- F Detergent Line Inlet

**Heat Source:** 500mm clearance from an external heat source is required in order to protect the oven control components. For clearances under 500mm, it is mandatory for Stoddart heat shields to be fitted while still maintaining a minimum clearance of 50mm to allow access to the unit. Failure to adhere to minimum clearances may void the oven warranty or add service costs due to lack of access.

**Non-Heat Source:** 50mm clearance from a non-heat source to allow access to the unit.

